

Solus and Link Gateway Technical Specifications

ITEMS	INFORMATION
Unit Dimension	
Width (mm)	120
Lenght (mm)	200
Height (mm)	60
Package Dimension	
Width (mm)	180
Lenght (mm)	270
Height (mm)	64
Weight	
Gross Weight (g) [Solus / LINK Gateway]	752 / 792
Net Weight (g) [Solus / LINK Gateway]	640 / 680
Power	
Operation Voltage (DC Volt)	9 – 36
Maximum Power Consumption (W)	3
Maximun Current (mA) @24 VDC	125
Average Current (mA) @24 VDC	96
Operating Environments	
Operating Temperature Range	-20°C to 60°C
Operating Relative Humidity Range	RH < 99%
Enclosure IP Rating	IP66
User Interface	
Keypad	5 Buttons
Display	Monochrome Graphic LCD 128 x 64
Sensor Input	
Sensor input type	Pressure level Sensor 4-20 mA
Number of Analog Input channel	4 Channels
Accuracy	+/- 0.5% (of total capacity)
Communication Port	
Ethernet Port	1 Port
RS485 Port	3 Ports
CAN Bus	2 Ports
Internet Connection (Modem)	1 Port
Communication Protocol	
Compatible Protocol	Modbus RTU, TCP/IP, CAN 2.0B